

672 & TJ

PRINTED CIRCUIT TEST POINT CONNECTORS

FOR .080" (2.03 MM) PROBE


1, 2, 4, 5, 6, 8, 12, 14, 16, 20, 21, 28, 30, 42, 56, 63 CONTACTS

Series 672 & TJ is described more comprehensively in our "672 & TJ" brochure.




C672-13-63
63 Contacts

NO. OF CONTACTS	PART NUMBER	CENTER SPACING	CURRENT RATING (AMPS)	BREAKDOWN SEA LEVEL (V. RMS)	TEST SEA LEVEL (V. RMS)
1	TJ4	N/A	7.5	—	2,000
	TJ6				
	TJ8		5	2,800	2,000
	TJ9				
2	TJ10	.200(5.08)	5	4,000	3,000
4	672-7-4	.156(3.96)	5	3,000	2,200
	672-16-4			2,200	1,650
	672-29-4			3,000	2,250
	C672-37-4			3,000	2,250
5	C672-18-5	.150(3.81)	5	2,200	1,650
	C672-20-5	.156(3.96)		2,500	1,875
	672-0-5			3,000	2,200
6	672-0-6	.156(3.96)	5	3,000	2,200
	672-4-6				
	672-4-1-6				
	672-6-6				
	C672-30-6				
8	C672-31-8	.156(3.96)	5	2,800	2,000
	L672-31-8			3,600	2,500
	C672-35-8			2,200	1,650
	C672-35-1-8			2,200	1,650
	C672-11-8	.200(5.08)		3,000	2,250
	C672-11-1-8				
	C672-11-2-8				
C672-11-3-8					
12	C672-36-12	.156(3.96)	5	2,000	1,500
	C672-36-1-12				
14	C672-14-14	.200(5.08)	5	3,000	2,500
	672-32P-14		7.5	4,000	3,000
	672-32S-14				
16	C672-9-16	.200(5.08)	5	3,000	2,250
	C672-17-16				
	C672-17-1-16				
	C672-17-2-16			5,000	3,750
	MSC672-17-2-16				
	C672-21-16				
C672-21-1-16	3,600	2,700			
20	C672-26-53-20	.164(4.17)	13	3,000	2,200
21	C672-34-21	.156(3.96)	5	2,200	1,650
28	C672-8-28	.200(5.08)	5	3,000	2,250
30	C672-27-53-30	.165(4.19)	13	3,000	2,200
42	C672-10-42	.380(9.65)	13	6,000	4,000
56	C672-38-56	.200(5.08)	5	4,000	3,000
	C672-39-56				
63	C672-13-63	.200(5.08)	5	3,000	2,250



672-0-6
6 Contacts



672-6-6
6 Contacts

Series 672 & TJ test point connectors have recessed and floating pin terminals mounted at right angle to the test socket. They dip solder to printed circuit boards with complete ease of alignment (except C672-10-42, 672-32P-14, C672-32S-14, C672-38-56, C672-39-56, C672-26-53-20 & C672-27-53-30, supplied with solder cup or taper pin terminations for direct wiring). Each socket grips and holds securely a standard .080" (2.03mm) test probe. The molded body can double as a convenient handle for insertion and withdrawal of printed circuit boards.



C672-17-16
16 Contacts



TJ4
1 Contact



TJ9
1 Contact



C672-31-8
8 Contacts